

Model: BDSA-125

## Arm Rests/Seat Cushion

Accessory Fits BDL-090



### WARNING

- When hunting from a treestand, falls can occur at any time which can cause injury or death. Use a fall arrest system at all times prior to leaving the ground. Never be detached from the tree at anytime.
- Please do not return this product to the retailer. Call BIG DOG TREESTANDS toll free (1-866-387-2002) for quick replacement of any damaged or missing parts.



Please inspect the shipping carton for evidence of damage or that it may have been opened before you received it. Then inspect your product carefully. Compare it to the image on the product label and the picture illustration in your instructions. You must check and tighten all bolts before each use. If for any reason you are not satisfied with the product, do not use it until the problem is solved or corrected.

### PACKING LIST:

<b>A</b>	2	Padded Arm Rest	Part # PAR-100
<b>B</b>	1	Seat Cushion	Part # SC-100
	4	6mm x 2" Bolt	Part # 1015
	4	6mm Locknut	Part # 2010

### ASSEMBLY INSTRUCTIONS

1. Attach the Padded Arm Rest(s) (Item A), so that the short side of the Padded Arm Rests is to the seat platform on each side and the long end is to the Connection Tube, bolt together using (4) 6mm x 2" bolts and locknuts. Note: The holes in the Padded Arm Rests should be aligned with front edge of the seat frame. These holes are used for a shooting rail accessory which can be purchased.
2. Check all Bolts on the stand and tighten securely.
3. Attach the Seat Cushion (Item B) to the Seat Platform by sliding the pocket on the front of the Seat Cushion over the front of the Seat Platform. Tie the straps around the seat platform tubes so that the Seat Cushion is securely fastened to the Seat Platform.

### WARNING

- Proper threading of straps is critical. Insure all straps are properly threaded and free of damage/wear prior to each use.
- Replace ALL straps (ratchet/button/stabilizing) annually and ALL Hardware (bolts/nuts/cables) every (2) years. Use only Big Dog Treestands certified replacement parts/components, all others are viewed as a modification to the product. Frequently lubricate all hardware/parts or as needed.
- Insure ALL contact points of the treestand/FAS are in contact/secured with the tree before climbing onto the platform. Always test/practice at ground level w/treestand and FAS until comfortable with use of the product.
- Inspect/insure ground under bottom ladder section is firm/level and all sections are connected/pinned together and the adjustable support bar is secured properly prior to each use and prior to leaving the ground. Do not use if sections are separated.
- It is advisable to replace all straps/ropes each time this product is removed from the tree or at least annually. Do not leave this product attached to any tree for more than (2) weeks due to tree growth.